

Pump 60Hz @ 3500 RPM

Series	Outside Diameter (Inches)	Pump Type	Max BHP Rating For Pump Shaft	Capacity Range Recommended Limits	
				(BPD)	(m3/D)
338	3.38"	SB-400	192	100-540	16-86
		SB-550	192	400-700	64-111
		SB-900	192	660-1060	105-168
		SB-1200	192	900-1650	143-262
		SB-1500	255	1000-2000	159-318
Minimum Casing Size: 4.5" Higher Volume Pumps Are Available					
400	4.00"	SH-300	192	100-450	16-72
		SH-450	192	350-550	56-87
		SH-750	192	550-960	89-152
		SH-1000	255	600-1250	95-199
		SH-1300	255	960-1640	153-261
		SH-1750	255	1200-2050	191-326
		SH-2150	255	1300-2600	207-413
		SH-3000	522	2000-3700	318-588
		SH-4000	522	3400-5200	541-827
		SH-5800	522	4400-7000	700-1113
SH-6000	522	3500-7500	556-1192		
Minimum Casing Size: 5.5" Higher Volume Pumps Are Available					
513	5.13"	SJ-2000	522	1650-2500	262-397
		SJ-2500	522	1800-3100	286-493
		SJ-3100	522	2200-3800	350-604
		SJ-4000	765	3200-4800	509-763
		SJ-5600	765	4000-7500	636-1192
		SJ-7000	765	5000-9000	795-1431
SJ-10000	1300	7000-12000	1113-1908		
Minimum Casing Size: 7" Higher Volume Pumps Are Available					
Larger Pumps are available as listed below. Please call for more information					
Series	Outside Diameter (Inches)	Min. Casing	Max BHP Rating For Pump Shaft	Capacity Range Recommended Limits (BPD)	(m3/D)
538	5.38"	7"	522-765	1300-10000	254-1590
562	5.63"	7"	765-1300	9200-36000	1463-5724
675	6.75"	8.625"	1300	4500-25000	715-3975
725	7.25"	9.625"	1300-2040	11000-54000	1749-8585
862	8.63"	10.75"	1300	12000-32500	1908-5167
950	9.5"	11.75"	2040	24000-47500	3816-7552
1000	10"	11.75"	2040	35000-64000	5565-10175
1125	11.25"	13.625"	2040	53600-96000	8522-15263